

MADE IN ITALY



INDUSTRIAL range



MiniCUBE

The smallest silent screw compressor



Fixed speed
2.2 kW




NEW

MINI CUBE

SILENT ROTARY SCREW COMPRESSOR

MADE IN ITALY

All the power of a screw compressor in one cubic meter



NEW



LOGIN ZERO

Multi-function controller with 5-digit LED display

Measures and displays:

- ▶ Compressor status (stand-by, idle, loaded, off).
- ▶ Operating temperature.
- ▶ Operating pressure.
- ▶ Total working hours and load hours.
- ▶ Remaining hours for maintenance.
- ▶ Alarm management (motor thermal overload, fan thermal overload, oil temperature values) with dedicated LED signalling.
- ▶ Auto-restart after power failure.
- ▶ Integrated digital phase sequence control.




MAXI Performance, MINI Dimensions.

only 65 dB(A)



2.2 kW



8 - 10 Bar



with continuous cycle



Reliable, compact, silent

MiniCUBE is the new oil-lubricated coaxial compressor with direct starter, the smallest of the entire FINI screw range. The small size of the air-end/motor connection system allows the machine to maintain an extremely small footprint. Furthermore, thanks to its extreme quietness, only 65 dB(A), it can be placed near any operating environment. MiniCUBE is available in the floor mounted version or on a painted or galvanized 90-litre tank.

Efficient and cost-effective


MiniCUBE is designed for continuous operation in industrial applications. The coaxial transmission, with the air-end directly connected to the electric motor without any flexible coupling, ensures the best transmission efficiency. The three-phase versions are equipped with an IE3 energy efficiency class motor. The FS14 air-end ensures minimum pressure losses, providing considerable energy savings and low operating and maintenance costs.

Easy to transport

MiniCUBE is handy and easy to move, thanks to the 2 sides handles (only floor mounted version) and the forklift or pallet truck pre-arrangement at the bottom of the tank.

Simplified maintenance

All internal components are easily accessible, making routine maintenance fast and simple to perform.



PLUG&PLAY
MiniCUBE is ready for use: it is supplied already equipped with RotarECOFLUID mineral oil.

	Model	Code	ℓ	Power supply		Air outflow rate			MAX		dB(A)	BSP	kg	L x W x H (mm)		kg	L x W x H (mm)	
				kW	HP	V/Ph/Hz	l/min.	m³/min.	c.f.m.	bar				psi	L		W	H
FLOOR MOUNTED	MiniCUBE 2.2-08	V51PC72FNM017	-	2.2	3	400/3/50	292	0.29	10.3	8	116	65	1/2"	68	780x460x600	79	840x540x790	
	MiniCUBE 2.2-08 M	V51PC60FNM017	-	2.2	3	230/1/50	292	0.29	10.3	8	116	65	1/2"	68	780x460x600	79	840x540x790	
	MiniCUBE 2.2-10	V51PK72FNM017	-	2.2	3	400/3/50	261	0.26	9.2	10	145	65	1/2"	68	780x460x600	79	840x540x790	
	MiniCUBE 2.2-10 M	V51PK60FNM017	-	2.2	3	230/1/50	261	0.26	9.2	10	145	65	1/2"	68	780x460x600	79	840x540x790	
PAINTED TANK	MiniCUBE 2.2-08-90	V72PC72FNM001	90	2.2	3	400/3/50	292	0.29	10.3	8	116	65	1/2"	104	730x460x1060	116	840x540x1340	
	MiniCUBE 2.2-08-90 M	V72PC60FNM001	90	2.2	3	230/1/50	292	0.29	10.3	8	116	65	1/2"	104	730x460x1060	116	840x540x1340	
	MiniCUBE 2.2-10-90	V72PK72FNM001	90	2.2	3	400/3/50	261	0.26	9.2	10	145	65	1/2"	104	730x460x1060	116	840x540x1340	
	MiniCUBE 2.2-10-90 M	V72PK60FNM001	90	2.2	3	230/1/50	261	0.26	9.2	10	145	65	1/2"	104	730x460x1060	116	840x540x1340	
GALVANIZED TANK	MiniCUBE 2.2-08-90 Z	V72PC72FNMZ01	90	2.2	3	400/3/50	292	0.29	10.3	8	116	65	1/2"	104	730x460x1060	116	840x540x1340	
	MiniCUBE 2.2-08-90 M Z	V72PC60FNMZ01	90	2.2	3	230/1/50	292	0.29	10.3	8	116	65	1/2"	104	730x460x1060	116	840x540x1340	
	MiniCUBE 2.2-10-90 Z	V72PK72FNMZ01	90	2.2	3	400/3/50	261	0.26	9.2	10	145	65	1/2"	104	730x460x1060	116	840x540x1340	
	MiniCUBE 2.2-10-90 M Z	V72PK60FNMZ01	90	2.2	3	230/1/50	261	0.26	9.2	10	145	65	1/2"	104	730x460x1060	116	840x540x1340	

M = Single-phase
Z = Galvanized tank

Reference conditions: air intake temperature 20°C (68°F) – atmospheric pressure 1 bar (14.5 p.s.i.).
Air flow was measured in the following operative pressures: 7.5 bar for models at 8 bar - 9.5 bar for models at 10 bar.
The data and results were measured in accordance with standard ISO 1217. The sound level was measured in accordance with standard ISO 3744.



Cod. 9990399 - 04/2024
Models and features in this catalogue may be subject to changes without prior notice.

A wide range of solutions for industrial applications



MICRO - PLUS
Oil-injected rotary screw compressors, with belt transmission, at fixed or variable speed, and power values from 2.2 to 75 kW.



K-MAX
Oil-injected rotary screw compressors, with direct transmission with or without gears, at fixed or variable speed, and power values from 5.5 to 90 kW.



TERA
Oil-injected rotary screw compressors, with direct driven, at fixed or variable speed, and power values from 110 to 250 kW.



OS Scroll
Oil-free compressors with scroll spiral pumps, at fixed speed, and power values from 2.2 to 30 kW.



AIR TREATMENT
Dryers, filters, vertical tanks, and a wide range of accessories for compressed air treatment.



The "Trust" warranty can be easily extended online through EasyConnect, the new Fini service portal specially created to simplify customers' lives by providing them with quick, clear responses about product availability, order management and goods shipping times.


Protect your investment, extend the warranty up to **5** years!

When installing your new Fini screw compressor, join the "Trust" Warranty 3- to 5-year extension program to benefit from countless advantages by maximising the effectiveness, safety and duration over time of your investment. Thanks to scheduled maintenance programs exclusively performed by FINI Authorised Assistance Centres, you can rely on timely, highly professional service, as well as on the use of only original spare parts guaranteed by the FSN brand.



FNA S.p.A. Via Einaudi, 6
10070 Robassomero Torino ITALY
T: +39 011 92 33 000 F: +39 011 92 41 138

BOLOGNA PLANT:
Via Toscana, 21 40069 Zola Predosa Bologna ITALY
T: +39 051 61 68 111 F: +39 051 75 24 08
info@fnacompressors.com
www.fnacompressors.com



AUTHORIZED DISTRIBUTOR:



a brand of



Follow us on:



finicompressors.com

